

NETWORK CAMERA

FID-2520RFP-36(28)

Indoor Dome Camera



특징

- Sony 최저조도 센서 적용 : IMX327
- Novatek SoC (NDAA Free)
- 상태 LED 적용
- 3축 가변 기구
- 30m IR거리 (High Power LED 4EA)
- H.264 / H.265 지원

사양

카메라	
Focus	Fixed
이미지센서	Sony 1/2.8" STARVIS CMOS 2MP Sensor (IMX327)
Number of Effective Pixel	1920 x 1080 Pixels
Min.Illumination	Color : 0.5 Lux BW(IR on) : 0 Lux
Operation	Operation
ICR for Day & Night	지원
IR LED	High Power 4 PCS
IR Distance	30M
OSD	Through Web
Day & Night	Auto / Color / BW
WDR	On / Off
Back Light Compensation	On / Off
3DNR	Auto
렌즈	3.6 mm Lens (2.8mm : option)
Motion Detection	지원
Privacy Mask	4 Blocks (On / Off)
Digital Zoom	x16 (On / Off)
Shutter Speed	Auto / Manual (1/30 ~ 1/30,000 Sec)
Slow shutter	Auto/Off
AGC	Auto
AWB	Auto / Manual/ATW
Image Effect	Mirror, Flip
Defog	On/Off

네트워크	
Ethernet	RJ-45 (10/100 Base-T)
Connection Mode	Fixed IP, DHCP,DDNS
Video compression	H.264/H.265/JPEG
Frame & Resolution	Max. 30 fps at 1920 x 1080
Dual-Stream	Main Stream(1080P) & Sub-Stream(D1)
Bitrate Control	CBR/VBR, Network Bandwidth Control
Protocol	TCP/IP, HTTP, RTP/RTSP, UDP, DHCP, FTP, SMTP, NTP, ARP, ICMP, DDNS, ONVi F
Security	WS-Security, RTSP Access Control
Max. User Access	up to 4
Onvif Compliance	지원
Remote Monitoring	All Kinds of Web Browser (I/E, Safari, Chrome, Firefox) CMS & MobileViewer (iPhone & Android)
Special Features	Special Features
PUSH Video Call	지원
Surge Protect	4kV
Status LED	Green(전송중)/RED(대기중)/Green깜빡임(모션)

일반	
Installation	Indoor
Operating Temp/Humidity	-10~50 °C / Less than 90% RH
General	General
Input Voltage	DC12V / PoE-802.3 af
Power Consumption	300mA
Dimension	130 x 130 x 77 mm (WxDxH)
Cable	없음 (내부커넥터)

(* 제품의 사양은 품질향상을 위해 사전 예고 없이 변경 될 수 있습니다.

외관

