

NETWORK CAMERA

FID-5550RFP-36(28)

5M Indoor Dome Camera



특징

- 5M IP카메라
- Sony 고해상도 Starvis 센서
- Novatek SoC (NDA Free)
- 상태 LED 적용
- 3축 가변 기구
- 30m IR거리 (High Power LED 4EA)
- H.264 / H.265 지원

사양

| 카메라 | |
|---------------------------|--------------------------------------|
| Focus | Fixed |
| 이미지센서 | Sony 1/2.8" STARVIS CMOS Sensor |
| Number of Effective Pixel | 3072 x 1728 Pixels |
| Min.Illumination | Color : 0.5 Lux BW(IR on) : 0 Lux |
| Operation | Operation |
| ICR for Day & Night | 지원 |
| IR LED | High Power 4 PCS |
| IR Distance | 30M |
| OSD | Through Web |
| Day & Night | Auto / Color / BW |
| WDR | On / Off |
| Back Light Compensation | On / Off |
| 3DNR | Auto |
| 렌즈 | 3.6 mm Lens (2.8mm : option) |
| Motion Detection | 지원 |
| Privacy Mask | 4 Blocks (On / Off) |
| Digital Zoom | x16 (On / Off) |
| Shutter Speed | Auto / Manual (1/30 ~ 1/30,000 Sec) |
| Slow shutter | Auto/Off |
| AGC | Auto |
| AWB | Auto / Manual/ATW |
| Image Effect | Mirror, Flip |
| Defog | On/Off |

| 네트워크 | |
|--------------------|---|
| Ethernet | RJ-45 (10/100 Base-T) |
| Connection Mode | Fixed IP, DHCP,DDNS |
| Video compression | H.264/H.265/MJPEG |
| Frame & Resolution | Max. 30 fps at 3072 x 1728 |
| Dual-Stream | Main Stream(5M) & Sub-Stream(D1) |
| Bitrate Control | CBR/VBR, Network Bandwidth Control |
| Protocol | TCP/IP, HTTP, RTP/RTSP, UDP, DHCP, FTP, SMTP, NTP, ARP, ICMP, DDNS, ONVi F |
| Security | WS-Security, RTSP Access Control |
| Max. User Access | up to 4 |
| Onvif Compliance | 지원 |
| Remote Monitoring | All Kinds of Web Browser (I/E, Safari, Chrome, Firefox) CMS & MobileViewer (iPhone & Android) |
| Special Features | Special Features |
| PUSH Video Call | 지원 |
| Surge Protect | 4kV |
| Status LED | Green(전송중)/RED(대기중)/Green깜빡임(모션) |

| 일반 | |
|-------------------------|------------------------------|
| Installation | Indoor |
| Operating Temp/Humidity | -10~50 °C / Less than 90% RH |
| General | General |
| Input Voltage | DC12V / PoE-802.3 af |
| Power Consumption | 300mA |
| Dimension | 130 x 130 x 77 mm (WxDxH) |
| Cable | 없음 (내부커넥터) |

(*) 제품의 사양은 품질향상을 위해 사전 예고 없이 변경 될 수 있습니다.

외관

