

NETWORK CAMERA

FIB-5550RFGP-36

5M Outdoor Bullet Camera



특징

- 5M IP카메라
- Sony 고해상도 Starvis 센서
- Novatek SoC (NDAA Free)
- 상태 LED 적용
- 3축 가변 기구
- 30m IR거리 ((High Power LED 4EA)
- H.264 / H.265 지원

사양

카메라	
Focus	Fixed
이미지센서	Sony 1/2.8" STARVIS CMOS Sensor
Number of Effective Pixel	3072 x 1728 Pixels
Min.Illumination	Color : 0.5 Lux BW(IR on) : 0 Lux
Operation	Operation
ICR for Day & Night	지원
IR LED	High Power 4 PCS
IR Distance	30M
OSD	Through Web
Day & Night	Auto / Color / BW
WDR	On / Off
Back Light Compensation	On / Off
3DNR	Auto
렌즈	3.6 mm Lens
Motion Detection	지원
Privacy Mask	4 Blocks (On / Off)
Digital Zoom	x16 (On / Off)
Shutter Speed	Auto / Manual (1/30 ~ 1/30,000 Sec)
Slow shutter	Auto/Off
AGC	Auto
AWB	Auto / Manual/ATW
Image Effect	Mirror, Flip
Defog	On/Off

네트워크	
Ethernet	RJ-45 (10/100 Base-T)
Connection Mode	Fixed IP, DHCP,DDNS
Video compression	H.264/H.265(추후 upgrade)/MJPEG
Frame & Resolution	Max. 30 fps at 3072 x 1728
Dual-Stream	Main Stream(5M) & Sub-Stream(D1)
Bitrate Control	CBR/VBR, Network Bandwidth Control
Protocol	TCP/IP, HTTP, RTP/RTSP, UDP, DHCP, FTP, SMTP, NTP, ARP, ICMP, DDNS, ONVIF
Security	WS-Security, RTSP Access Control
Max. User Access	up to 4
Onvif Compliance	지원
Remote Monitoring	All Kinds of Web Browser (I/E, Safari, Chrome, Firefox) CMS & MobileViewer (iPhone & Android)
Special Features	Special Features
PUSH Video Call	지원
Surge Protect	4kV
Status LED	Green(전송중)/RED(대기중)/Green깜빡임(모션)

일반	
Installation	Indoor/Outdoor
Weather Proof	Yes / IP68
Vandal Proof	-
Operating Temp/Humidity	-10~50 °C / Less than 90% RH
Built-in Fan & Heater	-
General	
Input Voltage	DC12V / PoE-802.3 af
Power Consumption	400mA
Dimension	193.9 x 67.8 x 75.8 mm (WxDxH)
Cable	DC jack / Ethernet /Reset

(**) 제품의 사양은 품질향상을 위해 사전 예고 없이 변경 될 수 있습니다.

외관

